



SOFTWARESILOS

Pricelist

PDF Manual

MODULE

pricelist

LAST UPDATED

2026-03-29

SOAP / REST API

Pricelist · [/pricelist/addons/rest-api](#)

Adds CRUD WebAPI endpoints for **pricelists** (pricelists, pricelist products, customer assignments, group assignments).

Package

- Composer package: `mageb2b/pricesystem-pricelist-api`
- Magento module: `MageB2B_PricesystemPricelistApi`

Installation

```
composer config bearer.repo.softwaresilo.io <token>
composer config repositories.softwaresilo composer
https://repo.softwaresilo.io/
composer require mageb2b/pricesystem-pricelist-api:*

php bin/magento setup:upgrade
php bin/magento cache:flush
```

Endpoints (Overview)

Pricelist endpoints:

Method	URL
GET	<code>/V1/pricesystem/pricelist/:id</code>
GET	<code>/V1/pricesystem/pricelist/search</code>
POST	<code>/V1/pricesystem/pricelist</code>
PUT	<code>/V1/pricesystem/pricelist/:id</code>
POST	<code>/V1/pricesystem/pricelistbulk</code>
DELETE	<code>/V1/pricesystem/pricelist/:id</code>
DELETE	<code>/V1/pricesystem/pricelist/all</code>

Pricelist product endpoints:

Method	URL
GET	<code>/V1/pricesystem/pricelistproduct/:id</code>
GET	<code>/V1/pricesystem/pricelistproduct/search</code>
POST	<code>/V1/pricesystem/pricelistproduct</code>
POST	<code>/V1/pricesystem/pricelistproductbulk</code>
PUT	<code>/V1/pricesystem/pricelistproduct/:id</code>
PUT	<code>/V1/pricesystem/pricelistproductbulk</code>

Method	URL
DELETE	/V1/pricesystem/pricelistproduct/:id

Customer assignment endpoints:

Method	URL
GET	/V1/pricesystem/pricelistcustomer/:id
GET	/V1/pricesystem/pricelistcustomer/search
POST	/V1/pricesystem/pricelistcustomer
PUT	/V1/pricesystem/pricelistcustomer/:id
DELETE	/V1/pricesystem/pricelistcustomer/:id
DELETE	/V1/pricesystem/pricelistcustomer/deleteByCustomerId/:customerId

Customer group assignment endpoints:

Method	URL
GET	/V1/pricesystem/pricelistgroup/:id
GET	/V1/pricesystem/pricelistgroup/search
POST	/V1/pricesystem/pricelistgroup
PUT	/V1/pricesystem/pricelistgroup/:id
DELETE	/V1/pricesystem/pricelistgroup/:id

Authentication

All endpoints above require a valid admin bearer token.

```
curl -X POST "https://your-store.com/rest/V1/integration/admin/token" \
-H "Content-Type: application/json" \
-d '{"username":"admin","password":"***"}'
```

Then call endpoints with:

```
-H "Authorization: Bearer <ADMIN_TOKEN>"
```

Request Payloads

The following payloads are the request wrappers expected by Magento WebAPI for this module.

Pricelist Requests

GET /V1/pricesystem/pricelist/:id

No request body.

GET /V1/pricesystem/pricelist/search

No request body. Use `searchCriteria` query parameters, for example:

```
/V1/pricesystem/pricelist/search?searchCriteria[filter_groups][0][filters][0][field]=name&searchCriteria[filter_groups][0][filters][0][value]=B2B&searchCriteria[filter_groups][0][filters][0][condition_type]=like&searchCriteria[currentPage]=1&searchCriteria[pageSize]=20
```

POST /V1/pricesystem/pricelist and PUT /V1/pricesystem/pricelist/:id use wrapper key pricelist:

```
{
  "pricelist": {
    "id": 12,
    "name": "B2B Winter 2026",
    "active": true,
    "priority": 10,
    "from_date": "2026-03-01",
    "to_date": "2026-12-31",
    "website_id": 1,
    "products": [
      {
        "product_id": "24-MB01",
        "qty": 1,
        "price": "49.90",
        "price_application_type": 1,
        "start": "2026-03-01",
        "end": "2026-12-31",
        "price_attribute_id": 77
      }
    ],
    "customers": "42,99",
    "groups": "1,3",
    "is_base_pricelist": false,
    "customer_attribute": "",
    "customer_attribute_value": "",
    "customer_address_attribute": "",
    "customer_address_attribute_value": "",
    "customer_attribute_combine": false
  }
}
```

POST /V1/pricesystem/pricelistbulk uses wrapper key pricelists:

```
{
  "pricelists": [
    {
      "name": "PL A",
      "active": true,
      "priority": 10,
      "website_id": 1
    },
    {
      "id": 12,
```

```

    "name": "PL B Updated",
    "active": true,
    "priority": 20,
    "website_id": 1
  }
]
}

```

For the `pricelist` object, `customers` and `groups` are REST input strings (comma-separated), not arrays. For assignment workflows, prefer the dedicated endpoints:

`/V1/pricesystem/pricelistcustomer*` and `/V1/pricesystem/pricelistgroup*`.

DELETE `/V1/pricesystem/pricelist/:id` and DELETE `/V1/pricesystem/pricelist/all`
No request body.

Pricelist Product Requests

GET `/V1/pricesystem/pricelistproduct/:id`
No request body.

GET `/V1/pricesystem/pricelistproduct/search`
No request body. Example:

```

/V1/pricesystem/pricelistproduct/search?searchCriteria[filter_groups][0][filters][0][field]=pricelist_id&searchCriteria[filter_groups][0][filters][0][value]=12&searchCriteria[filter_groups][0][filters][0][condition_type]=eq

```

POST `/V1/pricesystem/pricelistproduct` and PUT
`/V1/pricesystem/pricelistproduct/:id` use wrapper key `pricelistProduct`:

```

{
  "pricelistProduct": {
    "id": 55,
    "pricelist_id": 12,
    "product_id": "24-MB01",
    "qty": 1,
    "price": "49.90",
    "price_application_type": 1,
    "start": "2026-03-01",
    "end": "2026-12-31",
    "price_attribute_id": 77
  }
}

```

POST `/V1/pricesystem/pricelistproductbulk` and PUT
`/V1/pricesystem/pricelistproductbulk` use wrapper key `pricelistProducts`:

```

{
  "pricelistProducts": [
    {
      "id": 55,

```

```

    "pricelist_id": 12,
    "product_id": "24-MB01",
    "qty": 1,
    "price": "47.90",
    "price_application_type": 1
  },
  {
    "id": 56,
    "pricelist_id": 12,
    "product_id": "24-MB04",
    "qty": 5,
    "price": "37.90",
    "price_application_type": 5
  }
]
}

```

DELETE /V1/pricesystem/pricelistproduct/:id
No request body.

Pricelist Customer Assignment Requests

GET /V1/pricesystem/pricelistcustomer/:id
No request body.

GET /V1/pricesystem/pricelistcustomer/search
No request body. Example:

```

/V1/pricesystem/pricelistcustomer/search?searchCriteria[filter_groups][0][filters][0][field]=pricelist_id&searchCriteria[filter_groups][0][filters][0][value]=12&searchCriteria[filter_groups][0][filters][0][condition_type]=eq

```

POST /V1/pricesystem/pricelistcustomer and PUT
/V1/pricesystem/pricelistcustomer/:id use wrapper key pricelistCustomer:

```

{
  "pricelistCustomer": {
    "id": 90,
    "pricelist_id": 12,
    "customer_id": "alice@example.com"
  }
}

```

DELETE /V1/pricesystem/pricelistcustomer/:id and DELETE
/V1/pricesystem/pricelistcustomer/deleteByCustomerId/:customerId
No request body.

Pricelist Group Assignment Requests

GET /V1/pricesystem/pricelistgroup/:id
No request body.

GET /V1/pricesystem/pricelistgroup/search

No request body. Example:

```
/V1/pricesystem/pricelistgroup/search?searchCriteria[filter_groups][0][filters][0][field]=pricelist_id&searchCriteria[filter_groups][0][filters][0][value]=12&searchCriteria[filter_groups][0][filters][0][condition_type]=eq
```

POST /V1/pricesystem/pricelistgroup and PUT /V1/pricesystem/pricelistgroup/:id
use wrapper key `pricelistGroup`:

```
{
  "pricelistGroup": {
    "id": 77,
    "pricelist_id": 12,
    "group_id": 3
  }
}
```

DELETE /V1/pricesystem/pricelistgroup/:id

No request body.

Field Notes

- `price_application_type` values:
 - 1 = fixed
 - 2 = surcharge nominal
 - 3 = surcharge percent
 - 4 = discount nominal
 - 5 = discount percent
- `product_id` can resolve from ID or SKU, depending on `pricesystem/api/product_attribute_code`.
- `customer_id` can resolve from ID or email, depending on `pricesystem/api/customer_attribute_code`.
- `website_id` supports numeric website ID and website code.

For the full list, see: [Pricesystem SOAP / REST API](#)