



Configuration

PunchOut Documentation

Guide for Magento administrators, technical project owners, and implementation teams.

LAST UPDATED
2026-08-26

SOURCE
[Open this article online](#)

EXTENSION
[Magento 2 Extension Punchout](#)

Configuration

Open **Punchout > Configuration** and choose the correct website or store view before saving. Store-specific settings are important when buyers use different catalogs, currencies or security policies.

The screenshot shows the 'Configuration' page with a sidebar on the left containing links for CUSTOMERS, SALES, MAGEB2B, Punchout, SERVICES, and ADVANCED. The main content area is titled 'Configuration' and has a 'Save Config' button in the top right. The 'Security' section is active, showing the following settings:

- Require Strict Signature Validation** (store view): Yes
- Signature Secret** (store view):
- Allowed IP Ranges** (store view): 198.51.100.24/32
- One CIDR or IP per line.**
- Allow OCI request customer override** (store view): No
- Test-only: allow oci_customer_id parameter to select customer context.**
- Allow cXML request customer override** (store view): No
- Test-only: allow cxml_customer_id parameter to select customer context.**

General

Setting	Default	What it changes
Enable Punchout	Yes	Enables setup, cart, transfer, session and document processing for the selected scope.
Punchout return action label	Return to System	Replaces the checkout action during an active PunchOut storefront session.
Enable Sandbox Callback Mode	No	Exposes <code>/punchout/sandbox/callback</code> so a test return payload can be inspected. Never leave this on in production.

Security

Strict signature validation

Strict mode verifies an HMAC-SHA256 signature made with the configured signature secret. The caller sends the 64-character digest in **X-Punchout-Signature** or the **signature** parameter. A **sha256=** prefix is accepted.

This signature is a SoftwareSilo security layer, not a value that every OCI or cXML platform sends automatically. Enable it only after the procurement integration has implemented and verified the same signing rule. For a raw request body, sign that body. For parameter requests, the module removes the signature field, sorts associative keys and signs the normalized JSON representation.

Allowed IP ranges

Enter one IPv4/IPv6 address or CIDR range per line. An empty field permits requests from every source IP. In production, use the procurement provider's current outbound ranges and confirm that Magento sees the real client IP through your proxy or load balancer.

Request customer overrides

Allow OCI request customer override and **Allow cXML request customer override** allow request parameters to select a Magento customer. Both are disabled by default and labelled test-only. Keep them off in production; assign the customer on the buyer profile instead.

Outbound TLS

TLS certificate verification is enabled by default. **Allow insecure outbound TLS in sandbox mode** can disable certificate checks only while sandbox mode is active. It is intended for isolated test systems, not production.

Customer identity and JIT provisioning

The Store-view **Customer Identity** settings control whether customer-by-e-mail resolution can create an account when no Magento customer exists. Select the customer group used for those accounts before enabling JIT provisioning.

Each Buyer Profile selects one explicit resolution mode:

- **Guest** creates no Magento customer session;
- **Fixed Magento Customer** uses the selected customer;
- **Customer E-mail** resolves the e-mail extracted from the configured OCI or cXML source and can use JIT provisioning;
- **Optional Request Customer ID** uses a permitted request ID when present;
- **Required Request Customer ID** rejects a request without that ID.

Magento's configured account-sharing and account-confirmation policies remain authoritative. When confirmation is required, Magento sends its normal confirmation message and PunchOut cannot continue as that new account until it is confirmed.

Cart pricing

Allow inbound cart item prices is disabled by default. With that setting off, a price supplied to `/punchout/cart/add` is ignored and Magento calculates the product price. Enable buyer-supplied prices only when the integration contract requires them and the caller is trusted to set them.

cXML Profile Discovery

Profile Discovery is enabled by default for cXML 1.1 and 1.2 buyers. Magento builds the

response from the Store View and Buyer Profile instead of a separate transaction list.

Leave **Public PunchOut Base URL** empty when the Store View base URL is publicly correct. Set it only when a reverse proxy or external gateway exposes Magento under a different scheme or host. The value must not contain a query string or fragment.

The Buyer Profile's **Accept PunchOutSetupRequest** and **Accept OrderRequest** switches decide which transactions are advertised and accepted. See [cXML Profile Discovery](#).

Inbound Orders

These Store-view settings control an approved cXML [OrderRequest](#). They do not affect the earlier cart-return step.

Customer Identity



Cart



Inbound Orders



Processing Mode [store view] Acknowledge Only

Acknowledge Only records the request without creating a quote or order.

Authoritative Price Source [store view] Current Magento Pricing

Current Magento Pricing executes the normal customer-specific catalog and quote pricing pipeline.

Returned Cart Line Matching [store view] Auxiliary ID, then SKU

Used by snapshot-based pricing. Auxiliary ID is preferred when available.

Changed Quantity Action [store view] Recalculate with Magento

New Item Action [store view] Recalculate with Magento

Removed Item Action [store view] Allow Removal

Missing/Expired Snapshot Action [store view] Reject

Applies when snapshot-based pricing cannot resolve the original returned cart.

Price Mismatch Action [store view] Reject Order

Absolute Unit Price Tolerance [store view] 0.01

Difference in order currency allowed per unit.

Percent Unit Price Tolerance [store view] 0

Percentage difference allowed per unit. Either configured tolerance can permit the price.

Customer Resolution [store view] Buyer Profile Customer

Product Resolution [store view] Supplier Part ID

Address Source [store view] Incoming Order Addresses

Shipping Method [store view] [flatrate] Fixed

The selected method must be available for the resolved quote and destination.

Payment Method [store view] PunchOut Purchase Order

Defaults to the included offline method punchout_purchaseorder.

Order Update Policy [store view] Manual Review

Order Cancellation Policy [store view] Manual Review

Send Customer Order Email [store view] No

Send cXML ConfirmationRequest [store view] No

Sends a confirmation after Magento creates or cancels an order.

ASN URL [store view]

cXML endpoint that receives ShipNoticeRequest documents. This is not the PunchOut cart return URL.

Invoice URL [store view]

cXML endpoint that receives InvoiceDetailRequest documents. This is not the PunchOut cart return URL.

Supplier Credential Domain [store view]

cXML credential domain used for outbound ConfirmationRequest, InvoiceDetailRequest and ShipNoticeRequest messages.

Supplier Identity [store view]

Supplier Shared Secret [store view]

Maximum Processing Attempts [store view] 5

Retry Batch Size [global] 20

Retry Delay (minutes) [store view] 15

Outbound cXML Response Mode [store view] Allow Empty HTTP 2xx Response

Controls whether a successful HTTP response must include a valid cXML Response Status.

Inbound Order Payload Retention (days) [store view] 365

Removes retained request details after the configured period. Order identity and idempotency evidence are retained.

Returned Cart Snapshot Retention (days) [store view] 90

Must cover the longest expected requisition and approval workflow.

Processing and pricing

- **Processing Mode** chooses Acknowledge Only, Validate Only or Create Magento Order.
- **Authoritative Price Source** chooses current Magento pricing, the returned-cart snapshot, incoming prices or the hybrid original-if-unchanged policy.
- **Returned Cart Line Matching** uses auxiliary ID then SKU, or SKU only.
- **Changed Quantity, New Item, Removed Item** and **Missing Snapshot** settings decide whether Magento recalculates, allows, rejects or sends a request to manual review.
- **Price Mismatch Action** works with the absolute and percentage unit-price tolerances.

For most approval workflows, start with **Original Price if Unchanged; Otherwise Current Magento Price**. It keeps the price Magento returned for an unchanged line and sends changed quantities or new products through current customer-specific pricing.

Magento order context

Choose how Magento resolves the customer, product and addresses. Then select a shipping method and payment method available to the resulting quote. The included **PunchOut Purchase Order** method is intended for approved procurement orders.

Update and cancellation policies can reject a request, send it to manual review or perform their supported automatic action. **Send Customer Order Email** controls Magento's normal new-order email independently from cXML confirmation delivery.

Confirmation, document routing, retries and retention

Enable **ConfirmationRequest** only after the buyer has supplied a reachable HTTPS endpoint and supplier credentials are complete. Configure the ASN and Invoice URLs separately; neither document is sent to the browser cart-return URL. Buyer Profile URLs override the Store-view defaults. Retry settings control inbound processing attempts. Keep the returned-cart snapshot longer than the longest expected requisition and approval cycle.

Buyer-profile overrides take precedence over these Store-view values. Leave an override empty to inherit the selected Store view. See **Inbound Orders and Pricing** for the decision flow.

Trace and session

- **Enable Trace Logging** defaults to Yes. Payloads are sanitized before storage, but trace access should still be limited to integration and support administrators.
- **Trace Retention** defaults to 30 days. The daily cleanup job removes older traces.
- **Token Expiration** defaults to 2 hours and accepts decimal values such as **0.5**. Choose a duration long enough for the buyer's shopping flow. An invalid or non-positive value prevents context creation.

Analytics

Enable PunchOut Analytics controls the daily aggregates shown under **Punchout > Analytics**. The setting is enabled by default and follows Magento scope inheritance. The aggregates are independent of trace retention, so clearing old traces does not remove the reporting history.

Document Queue

The queue is enabled by default. Magento adds shipments and invoices belonging to PunchOut-created orders and delivers them to the effective Buyer Profile or Store-view ASN and Invoice URLs. Encrypted routing and payload data are retained with the order and queue row, so delivery does not depend on the expired browser session.

Setting	Default	Effect
Enable Queue Processing	Yes	Allows the five-minute cron job to process due documents.
Batch Size per Cron Run	20	Maximum due rows processed per store in one run.
Maximum Retry Attempts	5	Attempts recorded on a newly queued document.
Retry Delay	15 minutes	Delay before a failed row becomes eligible again.
Completed Queue Retention	365 days	Removes completed and failed operational queue rows after the selected period.

Definite HTTP failures follow the retry policy. A transport interruption after the request may have reached the receiver becomes **Delivery Unknown** and is not retried automatically. Verify the procurement system first, then use the separately protected Retry Unknown Delivery action only when another delivery is safe.

Retention and debug logging

Request replay retention is configurable and preserves completed results for safe idempotent retries. Inbound payload, returned-cart snapshot, trace and completed queue retention are configured independently. The cleanup batch size is a Default Config setting used by the daily retention job.

Store-scoped debug logging writes additional non-secret diagnostics to `var/log/punchout.log`. Enable it only during a controlled investigation and disable it afterward.

Frontend operation policy

The policy is enabled by default and applies different route lists to [create](#), [edit](#), [inspect](#), OCI [DETAIL](#) and OCI [DETAILADD](#) sessions. The supplied defaults allow normal catalogue and cart editing for [create](#) and [edit](#). Inspect reconstructs the supplied cart as read-only. DETAIL opens only the selected product, while DETAILADD allows that product's Add to Cart action and immediately returns the one selected line. Read [Storefront Operation Policy](#) before changing these lists; an incorrect full-action name can block a valid buyer journey.

For the literal configuration paths and field types, use [Admin Field Reference](#).